



EN ISO 20344:2011



ATLANTIDA
TERRANOVA
80128-01L

S3 HRO HI CI SRC

Size: 38-48
Weight: 860 gr.

Fit: 11

Working Environment:
Cold places, Mountains, Farming and Gardening, Wood-metal carpentry



FEATURES

UPPER

Full Grain leather Hydro 1,8-2,0 mm
Drummed leather Hydro 1,8-2,0 mm

LINING

GenuineWool Polar

INSOLE

Dual insulation

TOE CAP

CTC- Composite Toe Cap

RESISTANCE TO PERFORATION

Zero(K) Perforation resistant

SOLE

PU-RUBBER VIBRAM-HRO

Sole with anti-wear scaff cap. Outsole in VIBRAM rubber, resistant to 300° C by contact (HRO), to acids and oils. Design with self-cleaning outsole, with Antislip standard.

TECHNOLOGIES

Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



Protection elements

ZERO(k)

ANTIPERFORATION



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



SRC (SRA+SRB)



	SOLE 80 PU - RUBBER	
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.43 0.35
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19 0.13

EN ISO 20344:2011

Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.