



EN ISO 20345:2011



ENDURANCE

MONTANA

81156-00L

S3 SRC

Size: 36-48 Weight: 710 gr.

Fit: 11

Working Environment:

Building, Farming and Gardening,

fibercap **SX**t

Oil industry



Protection elements

FEATURES

UPPER

Full Grain-Anilina Leather-Hydro 1,8-2,0 mm

INSOLE

Dual insulation

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

SRC (SRA+SRB)

≥0.32

HEEL (CONTACT ANGLE 7°) ≥0.28

≥0.18

NTACT ANGLE 7° ≥0.13

SOLE 81 PU - PU

0.52

0.48

0.23

0.18

EN ISO 20344:201

TYPE

Half-knee Boot

SRA

DETERGENT SOLUTION

SRB GLYCEROL

SOLE

PU DUAL-DENSITY SRC

Two-component PU sole with antiwear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

TECHNOLOGIES

Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.





Composite toecap with fiberglass. Resistant to over 200J. Non metal

perforation resistant insert to over

the foot. Flexible and comfortable

. 1100 N with a 3.0 mm truncated cone

nail. Protection over the entire sole of

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater



Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.

