



EN ISO 20345:2011



SCOUT  
**LAVAREDO**  
30407-01L

**S3 HRO HI WR CI SRC**

**Size:** 36-50  
**Weight:** 830 gr.

**Fit:** 11

**Working Environment:**  
Building, Mountains, Farming and Gardening, Wood-metal carpentry



## FEATURES

### UPPER

No ladder H.T. Fabric  
MicroFiber TOP 1,8-2,0 mm  
MicroFiber Suede 1,8-2,0 mm

### LINING

3D Air circulation 320 gr.  
PrimaLoft® Footwear keeps your feet dry at all times, warm and comfortable, even in wet condition. The specially treated and water resistant fibers form a dynamic insulation structure, and the multi-diameter fibers build resiliency.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Dual insulation

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail - X Method

### TYPE

Ankle boot

### SOLE

#### PU-RUBBER VIBRAM-FIRE&ICE

PU foam insole, light and comfortable. Modular overtote to protect uppers. VIBRAM rubber tread with Fire & ICE mix for high performance in all temperatures. Self-cleaning design with special SRC grip.

## TECHNOLOGIES

### Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



### Protection elements



Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Lateral stability

dynamic **HC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



Wire Electricity Discharge


Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other



Padding with hi-tech yarns, light and efficient in keeping feet warm and dry. For particularly cold places.



## SRC (SRA+SRB)



SOLE 30  
PU - RUBBER

	FLAT ≥0.32	0.53
<b>SRA</b> CERAMIC DETERGENT SOLUTION	HEEL (CONTACT ANGLE °) ≥0.28	0.49
<b>SRB</b> STEEL GLYCEROL	FLAT ≥0.18	0.23
	HEEL (CONTACT ANGLE °) ≥0.13	0.18

EN ISO 20344:2011