△SKYTEC Ninja Flex[™]

LATEX GRIP GLOVE WITH A LIGHTWEIGHT LINER FOR A SUPERTHIN FEEL

The seamless lightweight liner and latex coating maintain an overall superthin feel for enhanced dexterity, fit and comfort. For manual handling in damp and dry conditions.

FEATURES

- The lightweight nylon/lycra liner (15 gauge) maintains a superthin 'feel' for improved dexterity, fit and comfort
- Anatomically designed for high levels of comfort and tactile touch
- > Abrasion and rip resistant
- > Excellent grip in both wet and dry environments
- > Silicone and lint free
- > Seamless liner prevents irritation









SUITABLE FOR

Typical Industries

- Construction
- Engineering
- Logistics
- Municipal Services
- Transport

Suitable Applications

- Assembly
- Final Fix
- Light Engineering
- Precision Operations

CERTIFICATION



2131X

See overleaf for explanation





△SKYTEC Ninja Flex[™]

PRODUCTION INFORMATION

MATERIALS	LINER:	15 gauge nylon
	COATING:	Natural Latex
COLOUR	Red/Grey	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL	SKY191 SKY192 SKY193 SKY194	10 pairs per bag 120 pairs per case

RECOMMENDATIONS FOR USE

- USE: General handling glove. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
- WARNING: Latex may cause allergies

CERTIFICATION LEGENDS

Abrasion Resistance



PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P | Impact Resistance | Straight Blade Cut Resistance (EN ISO: 13997) | Puncture Resistance | Circular Blade Cut Resi

MECHANICAL HAZARDS EN 388:2016

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)1618774747 F: +44 (0)1618774746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +97148829962 F: +97148829963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777)

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

© 2023 Globus (Shetland) Ltd | SKY-DATA-NINJA-FLEX-1123_1